



TOGGLE PADS - SOCKET


The IEC *Socket Toggle Pad* features an exclusive ball design that minimizes base separation. Ideal for heavy-duty load requirements. The threaded female socket allows use of your own stud or bolt. Integrated ball and swivel socket provide a low-friction support interface. Standard steel finish is corrosion resistant zinc-plated gold irridite. Other finishes available upon request.

Features

- Steel/stainless steel options
- Integrated ball and socket
- White Delrin (nylon) base option
- Black delrin available as custom item (change to -BD)

Applications

- Electronic equipment
- Enclosures
- Conveyors
- Fixtures / Tooling



TOGGLE PADS - STEEL & STAINLESS STEEL SOCKET

Steel	Stainless	Load	A	B	C	D	F	G
IL61-4G	IL61-4S	100	1/4-20	1/2	5/8	3/4	3/8	3/16
IL61-5G	IL61-5S	500	5/16-18	1/2	5/8	3/4	3/8	3/16
IL61-6G	IL61-6S	1000	3/8-16	1/2	5/8	3/4	3/8	3/16
IL61-7G	IL61-7S	2000	1/2-13	1/2	15/16	3/4	3/8	1/2
IL61-8G	IL61-8S	3000	5/8-11	5/8	1-1/8	3/4	1/2	5/8
IL61-9G	IL61-9S	4000	3/4-10	3/4	1-3/16	3/4	5/8	11/16
IL61-10G	IL61-10S	5000	1-8	1	1-1/4	3/4	11/16	3/4
IL63-4G	IL63-4S	100	1/4-20	1/2	5/8	1-1/4	3/8	3/16
IL63-5G	IL63-5S	500	5/16-18	1/2	5/8	1-1/4	3/8	3/16
IL63-6G	IL63-6S	1000	3/8-16	1/2	5/8	1-1/4	3/8	3/16
IL63-7G	IL63-7S	2000	1/2-13	1/2	15/16	1-1/4	3/8	1/2
IL63-8G	IL63-8S	3000	5/8-11	5/8	1-1/8	1-1/4	1/2	5/8
IL63-9G	IL63-9S	4000	3/4-10	3/4	1-3/16	1-1/4	5/8	11/16
IL63-10G	IL63-10S	5000	1-8	1	1-1/4	1-1/4	11/16	3/4

To order with 1/8" black rubber pad, (add "-P").

TOGGLE PADS (Delrin Base) - STEEL/STAINLESS STEEL SOCKET

Steel	Stainless	Load	A	B	C	D	F	G
IL61-4G-WD	IL61-4S-WD	100	1/4-20	1/2	5/8	3/4	3/8	3/16
IL61-5G-WD	IL61-5S-WD	300	5/16-18	1/2	5/8	3/4	3/8	3/16
IL61-6G-WD	IL61-6S-WD	500	3/8-16	1/2	5/8	3/4	3/8	3/16
IL61-7G-WD	IL61-7S-WD	750	1/2-13	1/2	15/16	3/4	3/8	1/2
IL61-8G-WD	IL61-8S-WD	1000	5/8-11	5/8	1-1/8	3/4	1/2	5/8
IL61-9G-WD	IL61-9S-WD	1250	3/4-10	3/4	1-3/16	3/4	5/8	11/16
IL61-10G-WD	IL61-10S-WD	1500	1-8	1	1-1/4	3/4	11/16	3/4
IL63-4G-WD	IL63-4S-WD	100	1/4-20	1/2	5/8	1-1/4	3/8	3/16
IL63-5G-WD	IL63-5S-WD	300	5/16-18	1/2	5/8	1-1/4	3/8	3/16
IL63-6G-WD	IL63-6S-WD	500	3/8-16	1/2	5/8	1-1/4	3/8	3/16
IL63-7G-WD	IL63-7S-WD	750	1/2-13	1/2	15/16	1-1/4	3/8	1/2
IL63-8G-WD	IL63-8S-WD	1000	5/8-11	5/8	1-1/8	1-1/4	1/2	5/8
IL63-9G-WD	IL63-9S-WD	1250	3/4-10	3/4	1-3/16	1-1/4	5/8	11/16
IL63-10G-WD	IL63-10S-WD	1500	1-8	1	1-1/4	1-1/4	11/16	3/4





TOGGLE PADS - METRIC SOCKET


The IEC *Metric Socket Toggle Pad* features an exclusive ball design that minimizes base separation. Ideal for heavy-duty load requirements. The threaded female socket allows use of your own stud or bolt. Integrated ball and swivel socket provide a low-friction support interface. Standard steel finish is corrosion resistant zinc-plated gold irridite. Other finishes available upon request.

Features

- Steel/stainless steel options
- Integrated ball and socket
- White Delrin (nylon) base option
- Black delrin available as custom item (change to -BD)

Applications

- Electronic equipment
- Enclosures
- Conveyors
- Fixtures / Tooling



METRIC TOGGLE PADS - STEEL & STAINLESS STEEL SOCKET

Steel	Stainless	Load	A	B	C	D	F	G
IL61-M6G	IL61-M6S	100	M6x1	1/2	5/8	3/4	3/8	3/16
IL61-M8G	IL61-M8S	500	M8x1.25	1/2	5/8	3/4	3/8	3/16
IL61-M10G	IL61-M10S	1000	M10x1.50	1/2	5/8	3/4	3/8	3/16
IL61-M12G	IL61-M12S	2000	M12x1.75	1/2	15/16	3/4	3/8	1/2
IL61-M16G	IL61-M16S	3000	M16x2.00	5/8	1-1/8	3/4	1/2	5/8
IL61-M20G	IL61-M20S	4000	M20x2.50	3/4	1-3/16	3/4	5/8	11/16
IL61-M24G	IL61-M24S	5000	M24x3.00	1	1-1/4	3/4	11/16	3/4
IL63-M6G	IL63-M6S	100	M6x1	1/2	5/8	1 1/4	3/8	3/16
IL63-M8G	IL63-M8S	500	M8x1.25	1/2	5/8	1 1/4	3/8	3/16
IL63-M10G	IL63-M10S	1000	M10x1.50	1/2	5/8	1 1/4	3/8	3/16
IL63-M12G	IL63-M12S	2000	M12x1.75	1/2	15/16	1 1/4	3/8	1/2
IL63-M16G	IL63-M16S	3000	M16x2.00	5/8	1-1/8	1 1/4	1/2	5/8
IL63-M20G	IL63-M20S	4000	M20x2.50	3/4	1-3/16	1 1/4	5/8	11/16
IL63-M24G	IL63-M24S	5000	M24x3.00	1	1-1/4	1 1/4	11/16	3/4

To order with 1/8" black rubber pad, (add "-P").

METRIC TOGGLE PADS (Delrin Base) - STEEL/STAINLESS STEEL SOCKET

Steel	Stainless	Load	A	B	C	D	F	G
IL61-M6G-WD	IL61-M6S-WD	100	M6x1	1/2	5/8	3/4	3/8	3/16
IL61-M8G-WD	IL61-M8S-WD	300	M8x1.25	1/2	5/8	3/4	3/8	3/16
IL61-M10G-WD	IL61-M10S-WD	500	M10x1.50	1/2	5/8	3/4	3/8	3/16
IL61-M12G-WD	IL61-M12S-WD	750	M12x1.75	1/2	15/16	3/4	3/8	1/2
IL61-M16G-WD	IL61-M16S-WD	1000	M16x2.00	5/8	1-1/8	3/4	1/2	5/8
IL61-M20G-WD	IL61-M20S-WD	1250	M20x2.50	3/4	1-3/16	3/4	5/8	11/16
IL61-M24G-WD	IL61-M24S-WD	1500	M24x3.00	1	1-1/4	3/4	11/16	3/4
IL63-M6G-WD	IL63-M6S-WD	100	M6x1	1/2	5/8	1 1/4	3/8	3/16
IL63-M8G-WD	IL63-M8S-WD	300	M8x1.25	1/2	5/8	1 1/4	3/8	3/16
IL63-M10G-WD	IL63-M10S-WD	500	M10x1.50	1/2	5/8	1 1/4	3/8	3/16
IL63-M12G-WD	IL63-M12S-WD	750	M12x1.75	1/2	15/16	1 1/4	3/8	1/2
IL63-M16G-WD	IL63-M16S-WD	1000	M16x2.00	5/8	1-1/8	1 1/4	1/2	5/8
IL63-M20G-WD	IL63-M20S-WD	1250	M20x2.50	3/4	1-3/16	1 1/4	5/8	11/16
IL63-M24G-WD	IL63-M24S-WD	1500	M24x3.00	1	1-1/4	1 1/4	11/16	3/4

